




Geberit AquaClean Mera Care Mera WC complete solution, floor-standing WC



APPLICATION PURPOSES

- For convenient and odourless toilet use
- For gently cleaning the anal and vaginal areas with water

CHARACTERISTICS

- Hybrid hot water system with continuous flow heater and storage water heater
- Anal shower with double-nozzle WhirlSpray shower technology
- Separate Lady shower nozzle in protected park position
- Adjustable shower water temperature
- Spray intensity can be set to five different levels
- Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Rimless WC ceramic appliance featuring TurboFlush flush technology
- Washdown WC with special glaze KeraTect
- User detection
- Odour extraction unit with run-on function
- Odour extraction with ceramic honey comb filter can be activated
- Dryer can be activated
- Dryer air intensity can be set to 5 positions

- Dryer arm can be extended
- Adjustable dryer temperature
- WC seat ring with soft-closing mechanism
- WC seat ring, fixed, for absorption of lateral forces
- Premounted sound insulation
- Functions and settings via remote control
- Three user profiles can be programmed
- Compatible with Geberit Home App
- External water supply connection, possible with accessories
- Mains connection with flexible three-core sheathed cable, on the right side, hidden behind the WC ceramic
- External mains connection with power outlet on the right possible
- With integrated exposed cistern
- Seat height adjustable between 44 and 56 cm
- Toilet flush can be triggered by remote control
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077

TECHNICAL DATA

Protection degree	IPX4
Nominal voltage	230 V AC
Mains frequency	50 Hz
Power consumption standby max.	0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C

Water temperature, adjustment range	34–40 °C
Flush volume, factory setting	6 / 4 l
Minimum flow pressure	0.5 bar
Calculated flow rate	0.03 l/s
Spray time	30–50 s
Belastung WC-Sitzring (kg) - max.	190 kg
Load WC seat max.	190 kg
Odour extraction unit	Yes
SoftOpening	No
With WC seat ring heating	No
With orientation light	No
With dryer functionality	Yes

SCOPE OF DELIVERY

- Female socket for mains connection
- Spray shield
- Descaling agent, 125 ml
- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted case and battery CR2032
- Fastening material
- Wall-mounted control panel for touchless activation

ACCESSORIES

- Geberit S-bend set for floor-standing WC

INFO

- This product is supplied with the Geberit AquaClean descaling agent. This consumable contains classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found at www.geberit.com.

- This product is only available via the Geberit Care Team. Please contact us for more information.

<i>Art. no.</i>	<i>Colour / surface</i>	<i>B cm</i>	<i>H cm</i>	<i>T cm</i>	<i>Protection class</i>	<i>Power consumption W</i>
146.242.11.1	WC ceramic appliance: white / KeraTect Design cover: white Cladding flushing cistern: high-pressure laminate white	40	44	59	I	2000